

1.	GENERAL INFORMATION		
1.1	Date updated:	Feb 26, 2020	
1.2	Vessel's name (IMO number):	Histria Agata (9357559)	
1.3	Vessel's previous name(s) and date(s) of change:	Not Applicable	
1.4	Date delivered/Builder (where built):	Jan 19, 2007/CONSTANTA SHIPYARD	
1.5	Flag/Port of Registry:	Malta/VALLETTA	
1.6	Call sign/MMSI:	9HSB8/256359000	
1.7	Vessel's contact details (satcom/fax/email etc.):	Pease contact operators	
1.8	Type of vessel (as described in Form A or Form B Q1.11 of the IOPPC):	Oil Tanker	
1.9	Type of hull:	Double Hull	
Ownership and Operation			
1.10	Registered owner - Full style:	ASTER SHIPPING CO LTD	
1.11	Technical operator - Full style:	Histria ShipManagement Srl Oborului Street 24,900162 Constanta Romania Tel: +40 241 694894 Fax: +40 241 694746 Email: office@histria.ro ; operations@histria.ro Web: www.histria.ro	
1.12	Commercial operator - Full style:	Histria ShipManagement Srl Oborului Street 24,900162 Constanta Romania Tel: +40 241 694894 Fax: +40 241 694746 Email: operations@histria.ro Web: www.histria.ro	
1.13	Disponent owner - Full style:	N/A	
Insurance			
1.14	P & I Club - Full Style:	Gard ASA	
1.15	P & I Club pollution liability coverage/expiration date:		Feb 20, 2021
1.16	Hull & Machinery insured by - Full Style: (Specify broker or leading underwriter)	LLOYD'S	
1.17	Hull & Machinery insured value/expiration date:		Jun 01, 2020
Classification			
1.18	Classification society:	DNV GL	
1.19	Class notation:	100 A5 Chemical tanker Type 3 Oil tanker with double hull BWM ERS ESP NAV-O RSD MC AUT EP-D Inert	
1.20	Is the vessel subject to any conditions of class, class extensions, outstanding memorandums or class recommendations? If yes, give details:	No N/A	
1.21	If classification society changed, name of previous and date of change:	N/A, Not Applicable	
1.22	Does the vessel have ice class? If yes, state what level:	No, n/a	
1.23	Date/place of last dry-dock:	Dec 19, 2019/CONSTANTA SHIPYARD	
1.24	Date next dry dock due/next annual survey due:	Jan 18, 2022	Apr 18, 2021
1.25	Date of last special survey/next special survey due:	Dec 22, 2016	Jan 18, 2022
1.26	If ship has Condition Assessment Program (CAP), what is the latest overall rating:	No,	
Dimensions			
1.27	Length overall (LOA):	179.96 Metres	
1.28	Length between perpendiculars (LBP):	172.00 Metres	
1.29	Extreme breadth (Beam):	32.20 Metres	
1.30	Moulded depth:	16.50 Metres	

1.31	Keel to masthead (KTM)/ Keel to masthead (KTM) in collapsed condition, if applicable:		44.30 Metres	n/a	
1.32	Distance bridge front to center of manifold:		62.35 Metres		
1.33	Bow to center manifold (BCM)/Stern to center manifold (SCM):		89.94 Metres	90.02 Metres	
1.34	Parallel body distances	Lightship	Normal Ballast	Summer Dwt	
	Forward to mid-point manifold:	27.74 Metres	40.60 Metres	48.80 Metres	
	Aft to mid-point manifold:	33.75 Metres	49.40 Metres	59.20 Metres	
	Parallel body length:	61.49 Metres	90 Metres	108 Metres	
Tonnages					
1.35	Net Tonnage:		11,369.00		
1.36	Gross Tonnage/Reduced Gross Tonnage (if applicable):		25,804.00	20,233	
1.37	Suez Canal Tonnage - Gross (SCGT)/Net (SCNT):		26,357.40	25,314.09	
1.38	Panama Canal Net Tonnage (PCNT):		21,516.00		
Loadline Information					
1.39	Loadline	Freeboard	Draft	Deadweight	Displacement
	Summer:	5.514 Metres	11.00 Metres	40,440 Metric Tonnes	50,029 Metric Tonnes
	Winter:	5.743 Metres	10.771 Metres	39,146 Metric Tonnes	48,825 Metric Tonnes
	Tropical:	5.285 Metres	11.229 Metres	41,559 Metric Tonnes	51,238 Metric Tonnes
	Lightship:	13.91 Metres	2.60 Metres	-	9,679.00 Metric Tonnes
	Normal Ballast Condition:	9.61 Metres	6.90 Metres	19,708.31 Metric Tonnes	29,387.31 Metric Tonnes
	Segregated Ballast Condition:	9.60 Metres	6.90 Metres	19,708.31 Metric Tonnes	29,387.31 Metric Tonnes
1.40	FWA/TPC at summer draft:		237 Millimetres	52.50 Metric Tonnes	
1.41	Does vessel have multiple SDWT? If yes, please provide all assigned loadlines:		Yes 37825 40440 39999 29999 34999		
1.42	Constant (excluding fresh water):		100 Metric Tonnes		
1.43	What is the company guidelines for Under Keel Clearance (UKC) for this vessel?		Pease contact operators		
1.44	What is the max height of mast above waterline (air draft)		Full Mast	Collapsed Mast	
	Summer deadweight:		33.378 Metres	n/a	
	Normal ballast:		37.10 Metres	n/a	
	Lightship:		41.70 Metres	n/a	

2.	CERTIFICATES	Issued	Last Annual	Last Intermediate	Expires
2.1	Safety Equipment Certificate (SEC):	Apr 05, 2018	Feb 28, 2019	Dec 19, 2019	Jan 18, 2022
2.2	Safety Radio Certificate (SRC):	Apr 05, 2018	Feb 28, 2019	Dec 19, 2019	Jan 18, 2022
2.3	Safety Construction Certificate (SCC):	Apr 05, 2018	Feb 28, 2019	Dec 19, 2019	Jan 18, 2022
2.4	International Loadline Certificate (ILC):	Dec 22, 2016		Jan 18, 2019	Jan 22, 2022
2.5	International Oil Pollution Prevention Certificate (IOPPC):	Apr 05, 2018	Feb 28, 2019	Dec 19, 2019	Jan 18, 2022
2.6	International Ship Security Certificate (ISSC):	Dec 09, 2016	Feb 28, 2019	Dec 19, 2019	Jan 18, 2022
2.7	Maritime Labour Certificate (MLC):	May 07, 2018	N/A	Not Applicable	Jul 03, 2023
2.8	ISM Safety Management Certificate (SMC):	Dec 09, 2016	Feb 28, 2019	Dec 19, 2019	Jan 18, 2022
2.9	Document of Compliance (DOC):	Dec 08, 2017			Oct 23, 2022
2.10	USCG Certificate of Compliance(USCGCOC):	-	-	-	-
2.11	Civil Liability Convention (CLC) 1992 Certificate:	Feb 20, 2020	N/A	N/A	Feb 20, 2021

2.12	Civil Liability for Bunker Oil Pollution Damage Convention (CLBC) Certificate:	Feb 20, 2020	N/A	N/A	Feb 20, 2021
2.13	Liability for the Removal of Wrecks Certificate (WRC):	Feb 20, 2020	N/A	N/A	Feb 20, 2021
2.14	U.S. Certificate of Financial Responsibility (COFR):	Jun 05, 2018	N/A	N/A	Jun 05, 2021
2.15	Certificate of Class (COC):	Apr 05, 2018	Feb 28, 2019	Dec 19, 2019	Jan 18, 2022
2.16	International Sewage Pollution Prevention Certificate (ISPPC):	Apr 05, 2018	N/A	N/A	Jan 18, 2022
2.17	Certificate of Fitness (COF):	Mar 27, 2018	Feb 28, 2019	Dec 19, 2019	Jan 18, 2022
2.18	International Energy Efficiency Certificate (IEEC):	Jan 28, 2015	N/A	N/A	N/A
2.19	International Air Pollution Prevention Certificate (IAPPC):	Apr 05, 2018	Feb 28, 2019	Dec 19, 2019	Jan 18, 2022

Documentation					
2.20	Owner warrant that vessel is member of ITOPF and will remain so for the entire duration of this voyage/contract:			Yes	
2.21	Does vessel have in place a Drug and Alcohol Policy complying with OCIMF guidelines for Control of Drugs and Alcohol Onboard Ship?			Yes	
2.22	Is the ITF Special Agreement on board (if applicable)?			Yes	
2.23	ITF Blue Card expiry date (if applicable):			May 30, 2020	

3.	CREW				
3.1	Nationality of Master:			Romanian	
3.2	Number and nationality of Officers:		7	Romanian	
3.3	Number and nationality of Crew:		10	ROMANIAN	
3.4	What is the common working language onboard:			Romanian and English	
3.5	Do officers speak and understand English?			Yes	
3.6	If Officers/ratings employed by a manning agency - Full style:		Officers: N/A	Ratings: N/A	

4.	FOR USA CALLS				
4.1	Has the vessel Operator submitted a Vessel Spill Response Plan to the US Coast Guard which has been approved by official USCG letter?			Yes	
4.2	Qualified individual (QI) - Full style:		Gallagher Marine Systems 200 Century Parkway, Suite 130 Mt. Laurel, NJ 08054 Tel: +1 703-683-4700 Fax: NA Email: info@chgms.com		
4.3	Oil Spill Response Organization (OSRO) - Full style:		USCG National Response Corporation 3500 Sunrise Highway, Suite T103 • Great River, New York 11739 Tel: +1 202 267 2675 Fax: 631-224 9082		
4.4	Salvage and Marine Firefighting Services (SMFF) - Full Style:		RESOLVE MARINE GROUP 1510 SE 17th Street Suite 400 Fort Lauderdale ,FL.33316 Tel: +1 954 764 8700 Web: www.resolveopa.com		

5.	SAFETY/HELICOPTER				
5.1	Is the vessel operated under a Quality Management System? If Yes, what type of system? (ISO9001 or IMO Resolution A.741(18) as amended):			Yes IMO Resolution A.741(18)	
5.2	Can the ship comply with the ICS Helicopter Guidelines?			Yes	
5.2.1	If Yes, state whether winching or landing area provided:			Winching	
5.2.2	If Yes, what is the diameter of the circle provided:			5.20 Metres	

6. COATING/ANODES					
6.1	Tank Coating	Coated	Type	To What Extent	Anodes
	Cargo tanks:	Yes	EPOXY / INTERLINE 704	Whole Tank	No
	Ballast tanks:	Yes	SIGMA MULTIMASTIC 440	Whole Tank	No
	Slop tanks:	Yes	EPOXY	Whole Tank	No

7. BALLAST					
7.1	Pumps	No.	Type	Capacity	At What Head (sg=1.0)
	Ballast Pumps:	2	Framo Centrifugal	600 Cu. Metres/Hour	25 Metres
	Ballast Eductors:	1	N/A	85 Cu. Metres/Hour	3 Metres

8. CARGO					
Double Hull Vessels					
8.1	Is vessel fitted with centerline bulkhead in all cargo tanks? If Yes, solid or perforated:			Yes, Solid	
Cargo Tank Capacities					
8.2	Number of cargo tanks and total cubic capacity (98%):			10 cargo tanks	46,820.60 Cu. Metres
8.2.1	Capacity (98%) of each natural segregation with double valve (specify tanks):			Seg#1: 7106.6 m3 (1P, 1S) Seg#2: 9866.1 m3 (2P, 2S) Seg#3: 10110.8 m3 (3P, 3S) Seg#4: 10109.8 m3 (4P, 4S) Seg#5: 9627.3 m3 (5P, 5S)	
8.2.2	IMO class (Oil/Chemical Ship Type 1, 2 or 3):			3	
8.3	Number of slop tanks and total cubic capacity (98%):			2	981.60 Cu. Metres
8.3.1	Specify segregations which slops tanks belong to and their capacity with double valve:			Independents: Cargo Tk 6P = 395.9 cbm Cargo Tk 6S = 585.7 cbm with double valve segregation	
8.3.2	Residual/retention oil tank(s) capacity (98%), if applicable:			189.70 Cu. Metres	
SBT Vessels					
8.3.3	What is total SBT capacity and percentage of SDWT vessel can maintain?			17,806.50 Cu. M	44 %
8.3.4	Does vessel meet the requirements of MARPOL Annex I Reg 18.2:			Yes	
Cargo Handling and Pumping Systems					
8.4	How many grades/products can vessel load/discharge with double valve segregation:			5	
8.4.1	State type of cargo containment (integral, independent, gravity or pressure tanks):			1P (Independent Pressure)	
8.5	Are there any cargo tank filling restrictions? If yes, specify number of slack tanks, max s.g., ullage restrictions etc.:			No Unless otherwise required by the Code the tanks may be filled up to 98% of their capacity, however, the cargo tanks are to be filled to such a level only that at the maximum temperature expected during transport sufficient expansion space is left. The following cargo density limitations apply: Tank Group A: 1.025t/m ³ @ 98%; 1.54t/m ³ for partial filling	
8.6	Max loading rate for homogenous cargo			With VECS	Without VECS
	Loaded per manifold connection:			2,500 Cu. Metres/Hour (If 12" VECS connection or lower as per	2,500 Cu. Metres/Hour (With minimum 6 COT opened

		Terminal restrictions)	simultaneously or lower as per Terminal restrictions)
	Loaded simultaneously through all manifolds:	3,750 Cu. Metres/Hour (If 12" VECS connection or lower as per Terminal restrictions)	3,750.00 Cu. Metres/Hour
Cargo Control Room			
8.7	Is ship fitted with a Cargo Control Room (CCR)?	Yes	
8.8	Can tank innage/ullage be read from the CCR?	Yes	
Gauging and Sampling			
8.9	Is gauging system certified and calibrated? If no, specify which ones are not calibrated:	Yes,	
	What type of gauging system as per IBC 13.1 is fitted (Open/Restricted/Closed)?	Closed	
	What type of fixed closed tank gauging system is fitted:	Radar	
	Is a tank overflow control system fitted? If yes, then state if system includes automatic closing of valves?	Yes, No	
	Are high level alarms fitted to the cargo tanks? If Yes, indicate whether to all tanks or partial:	Yes, All	
8.9.1	Can cargo be transferred under closed loading conditions in accordance with ISGOTT 11.1.6.6?	Yes	
8.9.2	Are cargo tanks fitted with multipoint gauging? If yes, specify type and locations:	Yes, 4 - MB 2", 1 fore, two middle, 1 aft	
8.10	Number of portable gauging units (example- MMC) on board:	4	
Vapor Emission Control System (VECS)			
8.11	Is a vapour return system (VRS) fitted?	Yes	
8.12	Number/size of VECS manifolds (per side):	2	254 Millimetres
8.13	Number/size/type of VECS reducers:	4 x 254/304.8 mm (10/12")	
Venting			
8.14	State what type of venting system is fitted:	Pres-Vac	
Cargo Manifolds and Reducers			
8.15	Total number/size of cargo manifold connections on each side:	5/304.80 Millimetres	
8.15.1	Does the vessel have a Common Line Manifold connection? If yes, describe:	yes - cross line	
8.16	What type of valves are fitted at manifold:	Butterfly / Manually	
8.17	What is the material/rating of the manifold:	STAINLESS STEEL/ANSI B16.5	
8.17.1	Does vessel comply with the latest edition of the OCIMF 'Recommendations for Oil Tanker Manifolds and Associated Equipment'?	Yes	
8.18	Distance between cargo manifold centers:	2,000.00 Millimetres	
8.19	Distance ships rail to manifold:	4,600.00 Millimetres	
8.20	Distance manifold to ships side:	4,600.00 Millimetres	
8.21	Top of rail to center of manifold:	800.00 Millimetres	
8.22	Distance main deck to center of manifold:	1,900.00 Millimetres	
8.23	Spill tank grating to center of manifold:	900.00 Millimetres	
8.24	Manifold height above the waterline in normal ballast/at SDWT condition:	11.50 Metres	7.90 Metres
8.25	Number/size/type of reducers:	10 x 406.4/304.8mm (16/12") 4 x 304.8/254mm (12/10") 4 x 304.8/203.2mm (12/8") 4 x 304.8/304.8mm (12/12") ANSI	
8.26	Is vessel fitted with a stern manifold? If yes, state size:	Yes, 304.80 Millimetres	
Heating			
8.27	Cargo/slop tanks fitted with a cargo heating system?	Type	Coiled
	Cargo Tanks:	deck heaters	No (heating coils only in slop tks;
			Material

				cargo tanks -heat exchangers on deck)	
	Slop Tanks:		HEATING COILS / stem	Yes	SS
8.27.1	Is a Thermal Oil Heating system fitted? If yes, identify tanks?			N/A,	
8.28	Maximum temperature cargo can be loaded/maintained:			70.0 °C / 158.0 °F	65 °C / 149 °F
8.28.1	Minimum temperature cargo can be loaded/maintained:			15 deg C above pour point	
Inert Gas and Crude Oil Washing					
8.29	Is an Inert Gas System (IGS) fitted/operational?			Yes/Yes	
8.29.1	Is a Crude Oil Washing (COW) installation fitted/operational?			Yes/Yes	
8.30	Is IGS supplied by flue gas, inert gas (IG) generator and/or nitrogen:			IG Generator	
8.30.1	If nitrogen generator, specify the applicable flow rate for each of the designed purity modes:				
Cargo Pumps					
8.31	How many cargo pumps can be run simultaneously at full capacity:			6	
8.32	Pumps	No.	Type	Capacity	At What Head (sg=1.0)
	Cargo Pumps:	10	Framo Centrifugal	500 M3/HR	125 Meters
		2	Framo Centrifugal	200 M3/HR	125 Meters
		1	Framo Centrifugal	150 M3/HR	125 Meters
		1	Framo Centrifugal	80 M3/HR	70 Meters
	Cargo Eductors:	0	N/A	0 Cu. Metres/Hour	
	Stripping:	1	Framo Reciprocating	30 Cu. Metres/Hour	100 Metres
8.33	Is at least one emergency portable cargo pump provided?			Yes	
Tank Cleaning Systems					
8.34	Is tank cleaning equipment fixed in cargo tanks?			Yes	
8.35	Is portable tank cleaning equipment provided?			Yes	
8.36	Tank washing pump capacity:			150.00 Cu. Metres/Hour	
8.37	Is a washing water heater fitted? If yes is it operational and state max washing water temperature:			Yes, Yes 85.00 Degrees Celsius	
8.38	What is the maximum number of machines that can be operated at their designed max pressure?			4	
Other Deck Equipment					
8.39	Is vessel fitted with a remote cargo tank temperature monitoring system. If yes, is it operational?			Yes, Yes	
8.40	Is vessel fitted with a remote cargo tank pressure monitoring system. If yes, is it operational?			Yes, Yes	
8.41	Is vessel fitted with a cargo tank drier. If yes is it operational and state capacity:			No, N/A	
8.42	Is vessel fitted with a cargo cooling system. If yes is it operational and state tanks applicable:			No, N/A	
8.43	Is steam available on deck?			No	

9.	MOORING					
9.1	Wires (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	n/a	n/a	n/a	n/a	n/a
	Main deck fwd:	n/a	n/a	n/a	n/a	n/a
	Main deck aft:	n/a	n/a	n/a	n/a	n/a
	Poop deck:	n/a	n/a	n/a	n/a	n/a
9.2	Wire tails	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	4	60.00 Millimetres	40% Polyester + 60% Nikasteel	11.00 Metres	75 Metric Tonnes
	Main deck fwd:	2	60.00 Millimetres	40% Polyester +	11.00 Metres	75 Metric Tonnes

				60% Nikasteel		
	Main deck aft:	2	60.00 Millimetres	40% Polyester + 60% Nikasteel	11.00 Metres	75 Metric Tonnes
	Poop deck:	4	60.00 Millimetres	40% Polyester + 60% Nikasteel	11.00 Metres	75 Metric Tonnes
9.3	Ropes (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	4	26.00 Millimetres	HMPE	220.00 Metres	55 Metric Tonnes
	Main deck fwd:	2	26.00 Millimetres	HMPE	220.00 Metres	55 Metric Tonnes
	Main deck aft:	2	26.00 Millimetres	HMPE	220.00 Metres	55 Metric Tonnes
	Poop deck:	4	26.00 Millimetres	HMPE	220.00 Metres	55 Metric Tonnes
9.4	Other lines	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	3	26.00 Millimetres	HMPE	220.00 Metres	55 Metric Tonnes
	Main deck fwd:			Not Applicable		
	Main deck aft:			Not Applicable		
	Poop deck:	3	26.00 Millimetres	HMPE	220.00 Metres	54 Metric Tonnes
9.5	Winches	No.	No. Drums	Motive Power	Brake Capacity	Type of Brake
	Forecastle:	2	Double Drums	Hydraulic	33.00 Metric Tonnes	manual type screw compressed band brake
	Main deck fwd:	1	Double Drums	Hydraulic	33.00 Metric Tonnes	manual type screw compressed band brake
	Main deck aft:	1	Double Drums	Hydraulic	33.00 Metric Tonnes	manual type screw compressed band brake
	Poop deck:	2	Double Drums	Hydraulic	33.00 Metric Tonnes	manual type screw compressed band brake
9.6	Bits, closed chocks/fairleads		No. Bits	SWL Bits	No. Closed Chocks	SWL Closed Chocks
	Forecastle:		8	64 Metric Tonnes	11	64 Metric Tonnes
	Main deck fwd:		2	46 Metric Tonnes	2	64 Metric Tonnes
	Main deck aft:		2	46 Metric Tonnes	6	64 Metric Tonnes
	Poop deck:		10	64 Metric Tonnes	19	64 Metric Tonnes
Anchors/Emergency Towing System						
9.7	Number of shackles on port/starboard cable:				12/12	
9.8	Type/SWL of Emergency Towing system forward:				ROLLS-ROYCE	200 Metric Tonnes
9.9	Type/SWL of Emergency Towing system aft:				COSALT 1000KN	100 Metric Tonnes
9.10.1	What is size of closed chock and/or fairleads of enclosed type on stern				600	
Escort Tug						
9.10.2	What is SWL of closed chock and/or fairleads of enclosed type on stern:				100.00 Metric Tonnes	
9.11	What is SWL of bollard on poop deck suitable for escort tug:				100.00 Metric Tonnes	
Lifting Equipment/Gangway						
9.12	Derrick/Crane description (Number, SWL and location):				Cranes: 1 x 10.00 Tonnes center	
9.13	Accommodation ladder direction:				Aft	
	Does vessel have a portable gangway? If yes, state length:				Yes, 13 Metres	
Single Point Mooring (SPM) Equipment						
9.14	Does the vessel meet the recommendations in the latest edition of OCIMF 'Recommendations for Equipment Employed in the Bow Mooring of Conventional Tankers at Single Point Moorings (SPM)':?				Yes	
9.15	If fitted, how many chain stoppers:				1	
9.16	State type/SWL of chain stopper(s):				TONGUE TYPE	200.00 Metric Tonnes

9.17	What is the maximum size chain diameter the bow stopper(s) can handle:	76.00 Millimetres
9.18	Distance between the bow fairlead and chain stopper/bracket:	3,300.00 Metres
9.19	Is bow chock and/or fairlead of enclosed type of OCIMF recommended size (600mm x 450mm)? If not, give details of size:	Yes 600 X 450

10.	PROPULSION		
10.1	Speed		Maximum Economical
	Ballast speed:	14 Knots (WSNP)	12.50 Knots (WSNP)
	Laden speed:	13 Knots (WSNP)	11.50 Knots (WSNP)
10.2	What type of fuel is used for main propulsion/generating plant:	VLSFO / MGO	VLSFO / MGO
10.3	Type/Capacity of bunker tanks:	Fuel Oil: 1,079.80 Cu. Metres Gas Oil: 424.00 Cu. Metres	
10.4	Is vessel fitted with fixed or controllable pitch propeller(s):	Fixed	
10.5	Engines	No	Capacity Make/Type
	Main engine:	1	8,230 Kilowatt 6550 MCC
	Aux engine:	3	880 Kilowatt 20L/975W WARSILA
	Power packs:	4	3,000 Cu. Metres 2x Cummings + 2x Siemens
	Boilers:	2	16.00 Metric Tonnes/Hour Saake Marine
Bow/Stern Thruster			
10.6	What is brake horse power of bow thruster (if fitted):	Yes, 1,155.00 bhp	
10.7	What is brake horse power of stern thruster (if fitted):	No,	
Emissions			
10.8	Main engine IMO NOx emission standard:	Tier I	
10.9	Energy Efficiency Design Index (EEDI) rating number:	n/a	

11.	SHIP TO SHIP TRANSFER	
11.1	Does vessel comply with recommendations contained in OCIMF/ICS Ship To Ship Transfer Guide (Petroleum, Chemicals or Liquefied Gas, as applicable)?	Yes
11.2	What is maximum outreach of cranes/derricks outboard of the ship's side:	4.75 Metres
11.3	Date/place of last STS operation:	Please contact operator

12.	RECENT OPERATIONAL HISTORY	
12.1	Last three cargoes/charterers/voyages (Last/2nd Last/3rd Last):	Please contact operator
12.2	Has vessel been involved in a pollution, grounding, serious casualty, unscheduled repair or collision incident during the past 12 months? If yes, provide details:	Pollution: No, n/a Grounding: No, n/a Casualty: No, n/a Repair: No, Not Applicable Collision: No,
12.3	Date and place of last Port State Control inspection:	Jan 31, 2020 / Novorrossisk
12.4	Any outstanding deficiencies as reported by any Port State Control? If yes, provide details:	No
12.5	Recent Oil company inspections/screenings (To the best of owners knowledge and without guarantee of acceptance for future business)*: * "Approvals" are not given by Oil Majors and ships are accepted for the voyage on a case by case basis.	Please contact operator
12.6	Date/Place of last SIRE inspection:	Please contact operator
12.6.1	Date/Place of last CDI inspection:	N/A
12.7	Additional information relating to features of the ship or operational characteristics:	

Revised 2018 ([INTERTANKO/Q88.com](http://www.intertanko.com))

Form completed on <http://www.q88.com/integration.aspx> Please email support@q88.com an updated copy if this is not the latest version.

To the best of owners knowledge all information is true and given without any guarantee.